



2017 TRX250X SPECIFICATIONS*

ENGINE	
Engine Type	229cc air-cooled OHV longitudinally mounted single-cylinder four-stroke
Bore And Stroke	68.5mm x 62.2mm
Induction	20mm piston-valve carburetor
Ignition	CD with electronic advance
Starter	Electric
DRIVE TRAIN	
Clutch	Honda SportClutch™
Transmission	Five-speed with Reverse
Driveline	Direct rear drive shaft
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 5.9 inches travel
Rear Suspension	Swingarm with single shock; 5.7 inches travel
Front Brake	Dual hydraulic 174mm discs
Rear Brake	Sealed mechanical drum
Front Tire	22 x 7-10 knobby
Rear Tire	22 x 10-9 knobby
DIMENSIONS	
Length	68.5 inches
Width	41.8 inches
Height	42.6 inches
Wheelbase	44.3 inches
Seat Height	31.4 inches
Ground Clearance	5.7 inches
Curb Weight	384 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	2.5 gallons, including 0.7-gallon reserve
Turning Radius	9.2 feet
OTHER	
Model Id	TRX250X
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	White, SE Red/White
Note	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.

*All figures are preliminary and subject to change.
 ©2016 American Honda Motor Co., Inc. – Motorcycle Division