



2016 FOURTRAX FOREMAN RUBICON 4X4 AUTOMATIC DCT EPS SPECIFICATIONS*

ENGINE	
Engine Type	475cc liquid-cooled OHV longitudinally mounted single-cylinder four-stroke engine
Bore And Stroke	92.0mm x 71.5mm
Induction	PGM-FI
Ignition	Full transistorized ignition
Starter	Electric with optional auxiliary recoil
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed automatic dual-clutch transmission with reverse
Driveline	Direct front and rear driveshafts with TraxLok® and locking front differential
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 7.28 inches travel
Rear Suspension	Independent dual-arm; 8.46 inches travel
Front Brakes	190mm hydraulic discs
Rear Brakes	170mm hydraulic disc
Front Tires	25 x 8-12
Front Tires	25 x 10-12
DIMENSIONS	
Length	84.5 inches
Width	47.4 inches
Height	48.6 inches
Wheelbase	50.9 inches
Seat Height	35.8 inches
Ground Clearance	9.4 inches
Curb Weight	719 lbs. (includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Towing Capacity	1322 pounds
OTHER	
Model Id	TRX500FA6
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	Red, Honda Phantom Camo®
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.

*All figures are preliminary and subject to change.
©2016 American Honda Motor Co., Inc. – Motorcycle Division