

## Specifications

### ■ Service Data

Tyre size	Front	70/90-17M/C 38P
	Rear	80/90-17M/C 50P
Tyre type		Bias-ply, tube
Recommended Tyres	Front	CHENG SHIN C-6016
	Rear	CHENG SHIN C-6016R
Tyre air pressure	Front	[Rider only] 200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
		[Rider and 1 passenger] 200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	[Rider only] 225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
		[Rider and 1 passenger] 280 kPa (2.80 kgf/cm <sup>2</sup> , 41 psi)
Spark plugs (standard)		CPR6EA-9S
Spark plug gap		0.80 to 0.90 mm (0.031 to 0.035 in)
Idle speed		1,400 ± 100 rpm
Recommended engine oil		Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," SAE 10W-30, JASO T 903 standard MA

Engine oil capacity	After draining	0.8 litres (0.8 US qt, 0.7 Imp qt)
	After disassembly	1.0 litres (1.1 US qt, 0.9 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	