

SPECIFICATIONS

DIMENSIONS

| | |
|----------------|--------------------|
| Overall length | 1,300 mm (51.2 in) |
| Overall width | 800 mm (31.5 in) |
| Overall height | 800 mm (31.5 in) |
| Wheelbase | 895 mm (35.2 in) |

WEIGHT

| | |
|------------|-------------------|
| Dry weight | 77 kg (169.8 lbs) |
|------------|-------------------|

CAPACITIES

| | |
|--------------|----------------------|
| Engine oil | 0.8 ℓ (0.8 U.S. qt) |
| Fuel tank | 4.3 ℓ (1.1 U.S. gal) |
| Reserve fuel | 0.9 ℓ (0.2 U.S. gal) |

ENGINE

| | |
|-----------------|--------------------------------------|
| Bore and stroke | 47.0 x 41.4 mm (1.850 x 1.630 in) |
|-----------------|--------------------------------------|

| | |
|---------------------------|---------------------------------|
| Compression ratio | 7.5 : 1 |
| Displacement | 72 cc (4.4 cu. in) |
| Contact breaker point gap | 0.3 ~ 0.4 mm (0.012 ~ 0.016 in) |
| Spark plug gap | 0.6 ~ 0.7 mm (0.024 ~ 0.028 in) |
| Valve tappet clearance | 0.05 mm (0.002 in) |

CHASSIS AND SUSPENSION

| | |
|---------------------------|-----------------|
| Caster angle | 20° |
| Trail length | 32 mm (1.26 in) |
| Tire size, front and rear | 16 x 8.0 - 7 |

POWER TRANSMISSION

| | |
|-------------------|-------|
| Primary reduction | 4.058 |
| Final reduction | 2.769 |
| Gear ratio, 1st | 3.273 |
| 2nd | 1.938 |
| 3rd | 1.350 |
| 4th | 1.043 |