

Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specially for O-ring chains. If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	20 to 30 mm (0.8 to 1.2 in)	
Standard drive chain	DID 520VF or RK 520KLO	
	No. of links	108
Standard sprocket sizes	Engine sprocket	14T
	Rear wheel sprocket	36T

■ Bulbs

Headlight	12V-60/55W
Brake/Tail light	12V-21/5W
Front turn signal lights	12V-21W × 2
Rear turn signal lights	12V-21W × 2
Position light	12V-5W
License plate light	12V-5W

■ Fuses

Main fuse	30A
Other fuses	30A, 15A, 10A

■ Torque Specifications

Engine oil drain bolt	24 N·m (2.4 kgf·m, 18 lbf·ft)
Oil filter cover bolts	12 N·m (1.2 kgf·m, 9 lbf·ft)
Rear axle nut	88 N·m (9.0 kgf·m, 65 lbf·ft)
Drive chain adjusting lock nuts	21 N·m (2.1 kgf·m, 15 lbf·ft)
Front axle nut	59 N·m (6.0 kgf·m, 44 lbf·ft)
Brake caliper mounting bolts	30 N·m (3.1 kgf·m, 22 lbf·ft)
Front axle pinch bolt	22 N·m (2.2 kgf·m, 16 lbf·ft)