



## Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains	
Drive chain slack	25 to 35 mm (1.0 to 1.4 in)	
Standard drive chain	RK 525SMOZ5	
	No. of links	108
Standard sprocket sizes	Engine sprocket	15T
	Rear wheel sprocket	44T

### ■ Bulbs

Headlight	12V-60/55W	
Brake/Tail light	LED	
Front turn signal lights	SI type	12V-21/5W x 2
	U type	12V-21W x 2
Rear turn signal lights	12V-21W x 2	
License plate light	12V-5W	

Specifications

### ■ Fuses

Main fuse	30A	
FI fuse	20A	
Other fuses	<b>CB400</b>	20A, 10A
	<b>CB400A</b>	30A, 20A, 10A

### ■ Torque Specifications

Engine oil drain bolt	30 N·m (3.1 kgf-m, 22 lbf-ft)
Oil filter	26 N·m (2.7 kgf-m, 19 lbf-ft)
Front axle bolt	59 N·m (6.0 kgf-m, 44 lbf-ft)
Front brake caliper fixing bolts	30 N·m (3.1 kgf-m, 22 lbf-ft)
Front axle pinch bolts	23 N·m (2.3 kgf-m, 17 lbf-ft)
Rear axle nut	88 N·m (9.0 kgf-m, 65 lbf-ft)