Specifications

■ Main Components

Туре	RC75	
Overall length	2,110 mm (83.1 in)	
Overall width	775 mm (30.5 in)	
Overall height	1,120 mm (44.1 in)	
Wheelbase	1,450 mm (57.1 in)	
Minimum ground clearance	150 mm (5.9 in)	
Caster angle	25° 30′	
Trail	101 mm (4.0 in)	
Curb weight	CB650F	206 kg (454 lb)
	CB650FA	208 kg (459 lb)
Maximum weight capacity*1	188 kg (414 lb)	
Maximum luggage weight	27 kg (60 lb)	
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	2.6 m (8.5 ft)	

^{*1} Including rider, passenger, all luggage, and accessories

Displacement	649 cm ³ (39.6 cu-in)		
Bore × stroke	67.0 × 46.0 mm (2.64 × 1.81 in)		
Compression ratio	11.4:1		
Fuel	Unleaded petrol Recommended: 91 RON or higher		
Tank capacity	17.3 litres (4.57 US gal, 3.81 Imp gal)		
Battery	FTZ10S 12V-8.6Ah (10 HR) / 9.1Ah (20 HR) YTZ10S 12V-8.6Ah (10 HR) / 9.1Ah (20 HR)		
Gear ratios	1st 2nd 3rd 4th 5th 6th	3.071 2.235 1.777 1.520 1.333 1.214	
Reduction ratios (primary / final)	1.690 / 2.800		