

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection (page 34) at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C: CLEAN R: REPLACE A: ADJUST

FREQUENCY		WHICHEVER COMES FIRST ↓	ODOMETER READING [NOTE (4)]							Refer to
			EVERY	600 mi (1,000 km)	4,000 mi (6,400 km)	8,000 mi (12,800 km)	12,000 mi (19,200 km)	16,000 mi (25,600 km)	20,000 mi (32,000 km)	
ITEMS	*									
		FUEL LINES			I	I	I	I	I	I
FUEL STRAINER		C	C	C	C	C	C	C	C	
THROTTLE OPERATION		I	I	I	I	I	I	I		
CARBURETOR-CHOKE			I	I	I	I	I	I		
AIR CLEANER	NOTE (1)			R		R		R		Page 51
CRANKCASE BREATHER	NOTE (2)		C	C	C	C	C	C		Page 52
SPARK PLUGS			R	R	R	R	R	R		Page 55
ENGINE OIL	YEAR	R	R	R	R	R	R	R		Page 53—54
ENGINE OIL FILTER	YEAR	R	R	R	R	R	R	R		Page 53—54
CARBURETOR- SYNCHRONIZATION		I	I	I	I	I	I	I		
CARBURETOR- IDLE SPEED		I	I	I	I	I	I	I		Page 56
EVAPORATIVE EMISSION CONTROL SYSTEM	NOTE (3)			I		I		I		