

## TUBELESS TYRES

This motorcycle is equipped with tubeless tyres, valves, and wheel rims. Use only tyres marked "TUBELESS" and tubeless valves on rims marked "TUBELESS TYRE APPLICABLE."

Proper air pressure will provide maximum stability, riding comfort and tyre life. Check tyre pressure frequently and adjust if necessary.

### NOTE:

- \* Tyre pressure should be checked before you ride while the tyres are "cold".
- \* Tubeless tyres have some degree of selfsealing ability if they are punctured, and leakage is often very slow. Inspect very closely for punctures, especially if the tyre is not fully inflated.

Tyre size	
Front	120/60 ZR17 (55W)
Rear	160/60 ZR17 (69W)
Cold tyre pressures kPa (kgf/cm <sup>2</sup> , psi)	Driver only
	Front 250 (2.50 , 36)
	Rear 290 (2.90 , 42)
	Driver and one passenger
Front 250 (2.50 , 36)	
Rear 290 (2.90 , 42)	
Tyre brand TUBELESS ONLY	BRIDGESTONE
	Front BT56F RADIAL
	Rear BT56R RADIAL
	MICHELIN
	Front MACADAM 90X
	Rear MACADAM 90X
DUNLOP	
Front D204FK	
Rear D204K	