


Recommended Fork Oil

suggested oil	KHL15-11 (KYB)
---------------	----------------

Fork Oil Change

Refer to *Front Suspension Disassembly* on page 118 for front suspension removal.

- Clean the fork assembly, especially the sliding surface of the slider and dust seal.
 - Hold the outer tube (1), then remove the fork damper (2) from the outer tube using the lock nut wrench (3). Gently slide the outer tube down onto the lower end of the slider (4).
- Lock nut wrench **070MA-MEN0100**




(1) outer tube
(2) fork damper

(3) lock nut wrench
(4) slider

NOTICE

The outer tube (1) can drop on the slider (5) and damage the fork dust seal (6). To avoid damage, hold both the outer tube and slider when removing the fork damper.



(1) outer tube
(5) slider

(6) fork dust seal


- Drain the fork oil from the outer tube (1). Drain the fork oil from the oil holes (7) of the fork damper.



(1) outer tube

(7) oil holes

- Drain the fork oil by turning the outer tube (1) upside down. (About 15.8 cm³ (0.5 US oz, 0.6 Imp oz) of fork oil will be left in the outer tube when it is left inverted for about 20 minutes at 20°C/68°F.)



(1) outer tube

Pour the drained oil into a suitable container and dispose of it in an approved manner (page 148).


NOTICE

Improper disposal of drained oil is harmful to the environment.

Amount of fork oil left in the fork (within damper and spring)

unit: cm³

minute °C/°F	5	10	20	35	55	85	145
0/32	24.6	22.0	19.4	17.7	16.5	15.5	14.0
10/50	22.7	19.8	17.6	16.0	14.8	13.9	12.4
20/68	21.5	18.1	15.8	14.0	13.1	12.0	10.8
30/86	20.5	16.8	14.9	13.1	11.8	11.0	9.7



(cont'd)