










# Optional Parts List

These parts and tools may be ordered from your authorized Honda dealer.

FRAME	Remarks
Driven sprocket Standard	< >: Drive chain links 48 Teeth, Aluminum. <116>
Optional	47 Teeth, Aluminum
	49 Teeth, Aluminum
Drive chain size/link	D.I.D 520 DMA4/120RB RK520TXZ/120RJ
Handlebar lower holder	3 mm offset
Optional	no offset

TOOLS	Remarks
Pin spanner A 	To adjust spring preload. (two spanners required)
Workstand 	For maintenance
Air gauge	For checking tyre air pressure

FRAME	Remarks
Shock spring Standard	54 N/mm (308.3 lbf/in)  Pink paint (aftermarket parts)
Optional Softer	52 N/mm (296.9 lbf/in)  Yellow paint
Stiffer	56 N/mm (319.8 lbf/in)  White paint
Fork spring Standard	4.6 N/mm (26.27 lbf/in)  No mark (factory products) or  4 scribe marks (aftermarket parts)
Optional Softer	4.4 N/mm (25.12 lbf/in)  2 scribe marks
Stiffer	4.8 N/mm (27.41 lbf/in)  6 scribe marks

The standard fork spring mounted on the motorcycle when it leaves the factory are not marked. Before replacing the springs, be sure to mark them so they can be distinguished from other optional springs.