SPECIFICATIONS

DIMENSIONS

Overall length 2.285 mm (89.9 in) Overall width 835 mm (32.9 in) 1.405 mm (55.3 in) Overall height Wheelbase 1,555 mm (61.2 in) Ground clearance 145 mm (5.7 in)

WEIGHT

Dry weight 293 kg (646 lbs)

CAPACITIES

Engine oil: After draining

After oil filter change After disassembly

Final drive gear oil Fuel tank

Cooling system capacity

Passenger capacity Maximum weight

capacity

3.6 ℓ (3.8 US qt, 3.2 Imp qt) 3.7 (3.9 US qt, 3.3 Imp qt) 4.3 ℓ (4.5 US qt, 3.8 Imp qt) 150 cc (5.1 oz) After draining 28 ℓ (7.4 US gal, 6.1 Imp gal) 3.0 ℓ (0.79 US gal, 0.66 lmp gal) Operator only, no passenger

195 kg (430 lb)

FNGINE

Bore and stroke $73 \times 64.8 \text{ mm} (2.87 \times 2.55 \text{ in})$ 10:1

Compression ratio Displacement 1,084 cc (66.1 cu.in)

Spark plug

Standard U24FER9 (NIPPONDENSO).

CR8EH9 (NGK)

For extended high U27FER9 (NIPPONDENSO),

speed riding CR9EH9 (NGK)

Spark plug gap 0.8—0.9 mm (0.031—0.035 in)

Idle speed $1,000 \pm 100 \text{ rpm}$