

# Specifications

<b>Chassis &amp; Suspension</b>		
caster		9.0°
trail		40 mm (1.6 in)
tyre size, front		AT22 × 7-10 ★★ DUNLOP KT171
tyre size, rear		AT22 × 10-9 ★ DUNLOP KT175
tyre pressure, front & rear (cold)	front	30 kPa (0.30 kgf/cm <sup>2</sup> , 4.4 psi)
	rear	20 kPa (0.2 kgf/cm <sup>2</sup> , 2.9 psi)
maximum tyre pressure, front & rear (cold)	front	34 kPa (0.34 kgf/cm <sup>2</sup> , 5.0 psi)
	rear	23 kPa (0.23 kgf/cm <sup>2</sup> , 3.3 psi)
minimum tyre pressure, front & rear (cold)	front	26 kPa (0.26 kgf/cm <sup>2</sup> , 3.8 psi)
	rear	17 kPa (0.17 kgf/cm <sup>2</sup> , 2.5 psi)

<b>Electrical</b>	
battery	12 V – 8 Ah
generator	0.123 kW/5,000 min <sup>-1</sup> (rpm)

<b>Lights</b>	
headlight (Low/High)	12 V 39/39 W
tail light	LED
neutral indicator	12 V – 3.0W
reverse indicator	12 V – 3.4W