

		FRONT	REAR
TYRE SIZE		AT22 × 7-11 ★	AT22 × 10-9 ★
TYRE BRAND		TRACKER HP GOOD YEAR	TRACKER HP GOOD YEAR
NO CARGO	RECOMMENDED PRESSURE	20 kPa (0.20 kgf/cm <sup>2</sup> , 2.9 psi)	20 kPa (0.20 kgf/cm <sup>2</sup> , 2.9 psi)
	MAXIMUM PRESSURE	23 kPa (0.23 kgf/cm <sup>2</sup> , 3.3 psi)	23 kPa (0.23 kgf/cm <sup>2</sup> , 3.3 psi)
	MINIMUM PRESSURE	17 kPa (0.17 kgf/cm <sup>2</sup> , 2.5 psi)	17 kPa (0.17 kgf/cm <sup>2</sup> , 2.5 psi)
WITH CARGO	RECOMMENDED PRESSURE	20 kPa (0.20 kgf/cm <sup>2</sup> , 2.9 psi)	20 kPa (0.20 kgf/cm <sup>2</sup> , 2.9 psi)

Fig. 4-31

Tyre specifications

## ⚠ WARNING

### POTENTIAL HAZARD

**Operating this ATV with improper tyres, or with uneven tyre pressure.**

### WHAT CAN HAPPEN

**Use of improper tyres on this ATV, or operation of this ATV with improper or uneven tyre pressure, may cause loss of control, increasing your risk of an accident.**

### HOW TO AVOID THE HAZARD

**Always use the size and type tyres specified in this Owner's Manual for this vehicle.**

**Always maintain proper tyre pressure as described in this Owner's Manual.**