## **SPECIFICATIONS**

DIMENSIONS		
Overall length Overall width Overall height Wheelbase	1,875 mm (73.8 in) 1,065 mm (41.9 in) 1,100 mm (43.3 in) 1,235 mm (48.6 in)	
WEIGHT		
Dry weight	215 kg (474 lbs)	
CAPACITIES		
Engine oil Fuel tank Fuel reserve capacity Passenger capacity	2.5 \( \empty( 2.6 US qt) \) 12.5 \( \empty( 3.3 US gal) \) 2.5 \( \empty( 0.7 US gal) \) Operator only	
ENGINE		
Bore and stroke  Compression ratio Displacement Spark plug gap  Valve clearance	74.0 x 65.5 mm (2.9 x 2.6 in) 9.0 : 1 281.7 cc (17.2 cu-in) 0.8-0.9mm (0.031-0.035 in) 0.15 mm (0.006 in)	

CHASSIS AND SUSPENSION	
Caster angle Trail length Tire size, Front: Rear:	2° 10 mm (0.39 in) AT 23 x 8-11 ★★ AT 24 x 9-11 ★
POWER TRANSMISSION	
Primary reduction Final reduction Front: Rear: Gear ratio, SL 1st 2nd 3rd 4th Reverse gear ratio	2.407 5.554 5.684 4.083 2.389 1.609 1.179 0.848 5.397

Noise level	82.0 dB (A) tested to comply with ISO 5131.
	comply with 13O 3131.