

## SPECIFICATIONS

<b>DIMENSIONS</b>	
Overall length	81.6 in (2,072 mm)
Overall width	46.6 in (1,184 mm)
Overall height	47.0 in (1,194 mm)
Wheelbase	50.7 in (1,287 mm)
<b>WEIGHT</b>	
Dry Weight	600 lbs (273 kg)
<b>CAPACITIES</b>	
Engine oil	5.8 US qt (5.5 ℓ , 4.8 Imp qt)
Cooling system	1.8 US qt (1.7 ℓ , 1.5 Imp qt)
Fuel tank	3.70 US gal (14.0 ℓ , 3.08 Imp gal)
Fuel reserve	1.00 US gal (3.8 ℓ , 0.84 Imp gal)
<b>ENGINE</b>	
Bore and stroke	3.62 × 2.95 in (92.0 × 75.0 mm)
Compression ratio	9.2 : 1
Displacement	30.41 cu-in (498.5 cm <sup>3</sup> )
Engine idle speed	1,400 ± 100 rpm
Spark plug, standard	IJR7A9 (NGK) VX22BC (DENSO)
Spark plug gap	0.03–0.04 in (0.8–0.9 mm)
Valve clearance, Intake	0.006 in (0.15 mm)
Exhaust	0.009 in (0.23 mm)
<b>CHASSIS AND SUSPENSION</b>	
Caster angle	3.0°
Trail length	0.5 in (12 mm)
Tire size, Front	AT25 × 8-12 ★★
Rear	AT25 × 10-12 ★★