

# Quick Reference

---

|                      |                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tires                | Front: AT25 × 8R12 ★★<br>Rear: AT25 × 10R12 ★★                                                                                                                                                                                                                                                                                                                                          |
| Tire Pressure (cold) | Front: 4.4 psi (30 kPa , 0.30 kgf/cm <sup>2</sup> )<br>Rear: 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> )<br>maximum tire pressure:<br>Front: 5.0 psi (34 kPa , 0.34 kgf/cm <sup>2</sup> )<br>Rear: 4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> )<br>minimum tire pressure:<br>Front: 3.8 psi (26 kPa , 0.26 kgf/cm <sup>2</sup> )<br>Rear: 3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> ) |
| Spark Plugs          | standard:<br>IFR5L11 (NGK) or<br>VK16PRZ11 (DENSO)<br>high speed riding:<br>IFR6L11 (NGK) or<br>VK20PRZ11 (DENSO)                                                                                                                                                                                                                                                                       |
| Coolant              | ethylene glycol antifreeze (silicate-free)<br>for aluminum engines in 50/50 solution<br>with Pro Honda HP Coolant or an<br>equivalent distilled water                                                                                                                                                                                                                                   |
| Fuses                | main 1: 30 A<br>main 2: 30 A<br>other: 20 A × 1, 10 A × 3                                                                                                                                                                                                                                                                                                                               |