

Torque Specifications

| | |
|--|---------------------------------|
| Grab rail mounting bolt | 27 N·m (2.8 kgf·m, 20 lbf·ft) |
| Engine oil drain bolt | 30 N·m (3.1 kgf·m, 22 lbf·ft) |
| Oil filter | 26 N·m (2.7 kgf·m, 19 lbf·ft) |
| Bearing holder pinch bolt | 88 N·m (9.0 kgf·m, 65 lbf·ft) |
| Seat adjust plate socket bolts A | 22 N·m (2.2 kgf·m, 16 lbf·ft) |
| Seat adjust set collar socket bolts B | 12 N·m (1.2 kgf·m, 9 lbf·ft) |
| Front wheel axle bolt | 59 N·m (6.0 kgf·m, 44 lbf·ft) |
| Front wheel brake caliper mounting bolts | 45 N·m (4.6 kgf·m, 33 lbf·ft) |
| Front wheel axle pinch bolts | 22 N·m (2.2 kgf·m, 16 lbf·ft) |
| Rear wheel nuts | 108 N·m (11.0 kgf·m, 80 lbf·ft) |
| Muffler band bolts | 21 N·m (2.1 kgf·m, 15 lbf·ft) |
| Muffler mounting nut | 27 N·m (2.8 kgf·m, 20 lbf·ft) |
| Front turn signal cover screws | 1.0 N·m (0.1 kgf·m, 0.7 lbf·ft) |

| | | |
|-----------------------------------|---|-----|
| Recommended drive chain lubricant | Drive chain lubricant designed specifically for O-ring chains. If not available, use SAE 80 or 90 gear oil. | |
| Drive chain slack | 25 to 35 mm (1.0 to 1.4 in) | |
| Standard drive chain | DID 525HV3 or RK 525ROZ6 | |
| Standard sprocket sizes | No. of links | 110 |
| | Engine sprocket | 16T |
| | Rear wheel sprocket | 43T |

Bulbs

| | |
|--------------------------|-------------|
| Headlight | LED |
| Brakelight | LED |
| Tail light | LED |
| Front turn signal lights | 12V-21W x 2 |
| Rear turn signal lights | 12V-21W x 2 |
| Position light | LED |
| License plate light | 12V-5W |

Fuses

| | |
|-------------|---------------|
| Main fuse | 30A |
| Other fuses | 30A, 20A, 10A |