



## Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains	
Drive chain slack	30 to 40 mm (1.2 to 1.6 in)	
Standard drive chain	DID 50VA8 or RK 50HFOZ5	
	No. of links	110
Standard sprocket sizes	Engine sprocket	16T
	Rear wheel sprocket	43T

### ■ Bulbs

Headlight	12V-55W x 2
Brakelight	LED
Tail light	LED
Front turn signal lights	12V-21W x 2
Rear turn signal lights	12V-21W x 2
Position light	12V-5W x 2
License plate light	12V-5W

### ■ Fuses

Main fuse	30A
Other fuses	30A, 20A, 10A

### ■ Torque Specifications

Engine oil drain bolt	30 N·m (3.1 kgf·m, 22 lbf·ft)
Oil filter	26 N·m (2.7 kgf·m, 19 lbf·ft)
Bearing holder pinch bolt	74 N·m (7.5 kgf·m, 55 lbf·ft)
Front wheel axle bolt	59 N·m (6.0 kgf·m, 44 lbf·ft)
Front wheel brake caliper mounting bolts	31 N·m (3.2 kgf·m, 23 lbf·ft)
Front wheel axle pinch bolts	22 N·m (2.2 kgf·m, 16 lbf·ft)
Rear wheel nuts	108 N·m (11.0 kgf·m, 80 lbf·ft)
Muffler band bolts	21 N·m (2.1 kgf·m, 15 lbf·ft)

Specifications