

TUBELESS TYRES

This motorcycle is equipped with tubeless tyres, valves, and wheel rims. Use only tyres marked "TUBELESS" and tubeless valves on rims marked "TUBELESS TYRE APPLICABLE."

Never mount tyres designed for use on automobiles on a motorcycle rim.

▲ WARNING

*** Any attempt to mount passenger car tyres on a motorcycle rim may cause the tyre bead to separate from the rim with enough explosive force to cause serious injury or death.**

Proper air pressure will provide maximum stability, riding comfort and tyre life. Check tyre pressure frequently and adjust if necessary.

NOTE:

* Tyre pressure should be checked before you ride while the tyres are "cold".

NOTE:

* Tubeless tyres have some degree of selfsealing ability if they are punctured, and leakage is often very slow. Inspect very closely for punctures, especially if the tyre is not fully inflated.

Tyre size		
Front	120/80 - 17 61S	
Rear	150/80 - 15 M/C 70S	
Cold tyre pressures kPa (kgf/cm ² , psi)	Driver only	
	Front	200 (2.00 , 29)
	Rear	200 (2.00 , 29)
	Driver and one passenger	
	Front	200 (2.00 , 29)
	Rear	200 (2.00 , 29)
Tyre brand TUBELESS ONLY	DUNLOP	
	Front	K555F
	Rear	K555
	BRIDGESTONE	
	Front	G701
	Rear	G702