

Safety Labels

< For USA >

TIRE INFORMATION	
Cold tire pressures:	
[Up to maximum weight capacity]	
Front	200kPa 2.00kg/cm ² 29psi
Rear	250kPa 2.50kg/cm ² 36psi
[Up to 90kg(200lbs) load]	
Front	200kPa 2.00kg/cm ² 29psi
Rear	200kPa 2.00kg/cm ² 29psi
Maximum weight capacity: 182kg(401lbs)	
Tire size: Front 120/90-17M/C 64S	
Rear 160/80-15M/C 74S	
Tire brand	Front Rear
DUNLOP	D404FG D404
BRIDGESTONE	G701 G702
CHENG SHIN	M6002 M6011R
Min. recommend tire center tread depth:	
Front 1.5mm (0.06in.) Rear 2.0mm (0.08in.)	
Read owner's manual.	

< For Canada >

TIRE INFORMATION	
Cold tire pressures:	
[Up to maximum weight capacity]	
Front	200kPa 2.00kg/cm ² 29psi
Rear	250kPa 2.50kg/cm ² 36psi
[Up to 90kg(200lbs) load]	
Front	200kPa 2.00kg/cm ² 29psi
Rear	200kPa 2.00kg/cm ² 29psi
Maximum weight capacity: 186kg(410lbs)	
Tire size: Front 120/90-17M/C 64S	
Rear 160/80-15M/C 74S	
Tire brand	Front Rear
DUNLOP	D404FG D404
BRIDGESTONE	G701 G702
CHENG SHIN	M6002 M6011R
Min. recommend tire center tread depth:	
Front 1.5mm (0.06in.) Rear 2.0mm (0.08in.)	
Read owner's manual.	

