

Service Data

Tyre size	Front	90/90-14M/C 46P
	Rear	100/90-14M/C 57P
Tyre type	Bias-ply, tubeless	
	Front	IRC SS-560F DUNLOP TT900F
Recommended Tyres	Rear	IRC SS-560R DUNLOP TT900A
	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure (Driver only)	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure (Driver and passenger)	Rear	250 kPa (2.50 kgf/cm ² , 36 psi)
	Front	1.5 mm (0.06 in)
Minimum tread depth	Rear	2.0 mm (0.08 in)
	(standard)	CPR7EA-9 (NGK)
Spark plug gap	0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	1,700 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil	
	API Service Classification SG or higher, excluding oils marked as "Energy Conserving,"	
	SAE 10W-30, JASO T 903 standard MB	

Engine oil capacity	After draining	0.8 litres (0.8 US qt, 0.7 Imp qt)
	After draining & cleaning strainer screen	0.9 litres (1.0 US qt, 0.8 Imp qt)
	After disassembly	0.9 litres (1.0 US qt, 0.8 Imp qt)
Transmission oil capacity	After draining	0.12 litres (0.13 US qt, 0.11 Imp qt)
	After disassembly	0.14 litres (0.15 US qt, 0.12 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	0.48 litres (0.51 US qt, 0.42 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	