

## TIRE RECOMMENDATION .....

- Off-the-road tires are standard on this model. Select the right tires in accordance with the following specifications:

Tire Brand	Bridge-stone	Front: TRAIL WING 5A Rear: TRAIL WING 5A
	Nitto	Front: NT-102B Rear: NT-102B
Tire size		Front: 2.75-21 Rear: 4.00-18
Tire inflation pressure (cold)		Front: 21 psi (1.5 kg/cm <sup>2</sup> ) Rear: 21 psi (1.5 kg/cm <sup>2</sup> )
Vehicle load limit		220 lbs (100 kg) operator only

When riding at any speed higher than **60 mph**, use the tires specified below:

Tire Brand	Bridge-stone	Front: TRAIL WING Rear: TRAIL WING
	Nitto	Front: NT-116 Rear: NT-116

- Over or under inflation of the tires causes abnormal tread wear or other defects which may result in serious accidents. Riding with under inflated tires will cause the tires to slip out of place in the rims, damaging the inner-tube valves. When running with a low air pressure below 14 psi (1kg/cm<sup>2</sup>), be sure to install rim locks (option) on the rear wheel.
- From time to time check tire pressure and correct it, if necessary.
- Replace the tires when the center block height of the tread is less than 0.15 in. (4 mm).