

Service data

Service data

Unit: mm (in)

Item	Specification
Lubrication	
Specified engine oil	Repsol 4T oil-stroke motorcycle oil SAE 10W-30
Engine oil capacity after draining	0.41 liter (0.43 US qt, 0.36 Imp qt)
after oil filter change	0.44 liter (0.46 US qt, 0.39 Imp qt)
after disassembly	0.60 liter (0.63 US qt, 0.53 Imp qt)
Specified transmission oil	ELF HTX740
Transmission oil capacity after draining	0.54 liter (0.57 US qt, 0.48 Imp qt)
after disassembly	0.57 liter (0.60 US qt, 0.50 Imp qt)
Fuel System	
Throttle body identification No.	GQPCA
Throttle grip free play	3 mm (0.1 in)
Engine idle speed	1,800 ± 100 min-1 (rpm)
Fuel pressure	294 kPa (2,99 kgf/cm ²) at idle
Fuel pump flow at 12 V	138 cm ³ minimum/10 seconds
Injector resistance	11.1 – 12.3 Ω (20 ° C/68 ° F)
Cooling System	
Recommended coolant	50/50 mixture coolant and distilled water
Radiator cap relief pressure	108 kPa (1,1 kgf/cm ²)

Item	Standard	Service limit
Cylinder Head/Valves		
Cylinder compression	460 kPa (4,7 kgf/cm ²)	– 0,05 (0,002)
Cylinder head warpage	–	–
Valve clearance	0,12 ± 0,03 (0,005 ± 0,001)	–
	0,30 ± 0,03 (0,012 ± 0,001)	–
Valve stem O.D.	4,475 – 4,490 (0,1762 – 0,1768)	4,470 (0,1760)
	4,465 – 4,480 (0,1758 – 0,1764)	4,460 (0,1756)
Valve guide I.D.	4,500 – 4,512 (0,1772 – 0,1776)	4,552 (0,1792)
Valve stem-to-guide clearance		
	0,010 – 0,037 (0,0004 – 0,0015)	–
	0,020 – 0,047 (0,0008 – 0,0019)	–
Valve guide projection	8,0 – 8,3 (0,31 – 0,33)	–
above cylinder head	8,2 – 8,5 (0,32 – 0,33)	–
Valve spring free length	25,41 (1,000)	24,9 (0,98)
	28,32 (1,115)	27,6 (1,09)
Rocker arm I.D.	10,000 – 10,015 (0,3937 – 0,3943)	10,051 (0,3957)
Rocker arm shaft O.D.	9,972 – 9,987 (0,3926 – 0,3932)	9,925 (0,3907)
Rocker arm-to-shaft clearance	0,013 – 0,043 (0,0005 – 0,0017)	0,11 (0,04)
Cam lobe height	32,011 – 33,051 (1,2603 – 1,3012)	31,871 (1,2548)
	32,855 – 32,935 (1,2935 – 1,2967)	32,748 (1,2893)