

Specifications

■ Service Data

Tyre size	Front	80/90-14M/C 40P
	Rear	90/90-14M/C 46P
Tyre type		Bias-ply, tubeless
Recommended Tyre	Front	SRI FT235
	Rear	SRI FT235
Tyre air pressure		[Driver only]
	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
		[Driver and passenger]
		200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure		[Driver only]
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
		[Driver and passenger]
		225 kPa (2.25 kgf/cm ² , 33 psi)
Spark plug	(standard)	MR9C-9N (NGK) or U27EPR-N9 (DENSO)
Spark plug gap		0.8 to 0.9 mm (0.03 to 0.04 in)
Idle speed		1,700 ± 100 rpm

Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving" SAE 10W-30, JASO T 903 standard MB	
	After draining	0.7 litres (0.7 US qt, 0.6 Imp qt)
Engine oil capacity	After disassembly	0.8 litres (0.8 US qt, 0.7 Imp qt)
	After draining	0.10 litres (0.11 US qt, 0.09 Imp qt)
Transmission oil capacity	After disassembly	0.12 litres (0.13 US qt, 0.11 Imp qt)
	Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid