

## Specifications

### ■ Service Data

Tyre size	Front	110/80-14M/C 53P
	Rear	130/70-13M/C 57P
Tyre type	Bias-ply, tubeless	
	Recommended	SRI FT297
Tyres	Front	SRI FT297
	Rear	SRI FT297
Tyre air pressure (Drivers only)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
Tyre air pressure (Driver and passenger)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plug	MR8K-9 (NGK)	
Spark plug gap	0.8 - 0.9 mm (0.03 - 0.04 in)	
Idle speed	1,700 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MB	

Engine oil capacity	After draining	0.8 L (0.8 US qt, 0.7 Imp qt)
	After draining & cleaning strainer screen	0.8 L (0.8 US qt, 0.7 Imp qt)
Transmission oil capacity	After disassembly	0.9 L (1.0 US qt, 0.8 Imp qt)
	After draining	0.12 L (0.13 US qt, 0.11 Imp qt)
Recommended brake fluid	After disassembly	0.14 L (0.15 US qt, 0.12 Imp qt)
	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	0.48 L (0.51 US qt, 0.42 Imp qt)	
	Recommended HONDA PRE-MIX COOLANT	