Items			Frequency*1								
			× 1,000 mi	0.6	4	8	12	16	20	24	Refer to
		× 1,000 km	1.0	6.4	12.8	19.2	25.6	32.0	38.4	page	
Brake	e Fluid*4				1	1	ß	1	1	B	70
Brake	e Pads Wear										71
ے Brake	e System			1		1		1		1	70
Brake	Light Switch	1									-
ਮ Head	light Aim	1				1		1		1	-
를 Clutch	h System										79
Non-Emission-Related Clutch Side S Suspe	h Fluid*4				1	1	ß	1	1	ß	73
Side S	Stand									1	74
Suspe	ension	*				1				1	80
ĕ _{Nuts,}	Bolts, Fasteners	1									-
Whee	els/Tires	*				1		1		1	50
Steeri	ing Head Bearings	*									-

Maintenance Legend

: Inspect (clean, adjust, lubricate, or replace, if necessary)

C : Clean
R : Replace

L : Lubricate

Notes:

*1: At higher odometer readings, repeat at the frequency interval established here.

- *2 : Service more frequently when riding in unusually wet or dusty areas.
- *3 : Service more frequently when riding in rain or at full throttle.
- *4 : Replace every 2 years, or at indicated odometer intervals, whichever comes first. Replacement requires mechanical skill.
- *5: USA only.