

| | | |
|------------------------|-----------------|-----|
| Standard sprocket size | Drive sprocket | 14T |
| | Driven sprocket | 36T |

■ Bulbs

| | |
|-------------------------|---------------|
| Headlight | 12 V-60/55 W |
| Brake light/Taillight | 12 V-21/5 W |
| Front turn signal light | 12 V-21 W x 2 |
| Rear turn signal light | 12 V-21 W x 2 |
| License plate light | 12 V-5 W |

■ Fuses

| | |
|------------|---------------------------------|
| Main fuse | 30 A |
| Other fuse | CB300F 15 A, 10 A |
| | CB300FA 30 A, 15 A, 10 A |

■ Torque Specifications

| | |
|--------------------------------|---------------------------------|
| Oil filter cover bolt | 9 lbf-ft (12 N·m, 1.2 kgf-m) |
| Engine oil drain bolt | 18 lbf-ft (24 N·m, 2.4 kgf-m) |
| Air cleaner case cover screw | 0.8 lbf-ft (1.1 N·m, 0.1 kgf-m) |
| Rear axle nut | 65 lbf-ft (88 N·m, 9.0 kgf-m) |
| Drive chain adjusting lock nut | 15 lbf-ft (21 N·m, 2.1 kgf-m) |
| Front axle nut | 44 lbf-ft (59 N·m, 6.0 kgf-m) |
| Brake caliper mounting bolt | 22 lbf-ft (30 N·m, 3.1 kgf-m) |
| Front axle pinch bolt | 16 lbf-ft (22 N·m, 2.2 kgf-m) |