

Specifications

■ Main Components

| | |
|---------------------------|------------------------------|
| Type | PC45 |
| Overall length | 81.9 in (2,080 mm) |
| Overall width | 31.1 in (790 mm) |
| Overall height | 41.7 in (1,060 mm) |
| Wheelbase | 55.5 in (1,410 mm) |
| Minimum ground clearance | 6.3 in (160 mm) |
| Caster angle | 25° 30' |
| Trail | 4.0 in (102 mm) |
| Curb weight | CB500F |
| | 49 STATE 414 lb (188 kg) |
| | 50 STATE 417 lb (189 kg) |
| | (meets California) |
| CB500FA | 50 STATE 421 lb (191 kg) |
| | (meets California) |
| | Canada model 419 lb (190 kg) |
| Maximum weight capacity*1 | 370 lb (168 kg) |
| Passenger capacity | Rider and 1 passenger |
| Minimum turning radius | 8.9 ft (2.7 m) |

*1 Including rider, passenger, all luggage, and accessories

| | |
|------------------------------------|--|
| Displacement | 28.7 cu-in (471 cm ³) |
| Bore x stroke | 2.64 x 2.63 in (67.0 x 66.8 mm) |
| Compression ratio | 10.7:1 |
| Fuel | Unleaded gasoline Recommended: 86 PON or higher |
| Tank capacity | 4.41 US gal (16.7 liters) |
| Battery | FTZ10S |
| | 12V-8.6Ah (10 HR) |
| | YTZ10S |
| | 12V-8.6Ah (10 HR) |
| Gear ratios | 1st 3.285 |
| | 2nd 2.105 |
| | 3rd 1.600 |
| | 4th 1.300 |
| | 5th 1.150 |
| | 6th 1.043 |
| Reduction ratios (primary / final) | 2.029 / 2.733 |