

Specifications

■ Main Components

Type	PC46	
Overall length	82.5 in (2,095 mm)	
Overall width	32.7 in (830 mm)	
	Windscreen position	
Overall height	Low	49.6 in (1,260 mm)
	High	50.8 in (1,290 mm)
Wheelbase	55.9 in (1,420 mm)	
Minimum ground clearance	6.7 in (170 mm)	
Caster angle	26° 30'	
Trail	4.3 in (108 mm)	
Curb weight	CB500X	425 lb (193 kg)
	CB500XA	
	50 STATE (meets California)	430 lb (195 kg)
	Canada model	428 lb (194 kg)
Maximum weight capacity*1	377 lb (171 kg)	
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	9.2 ft (2.8 m)	

*1 Including rider, passenger, all luggage, and accessories

Displacement	28.7 cu-in (471 cm ³)	
Bore x stroke	2.64 x 2.63 in (67.0 x 66.8 mm)	
Compression ratio	10.7:1	
Fuel	Unleaded gasoline Recommended: 86 PON or higher	
Tank capacity	4.57 US gal (17.3 liters)	
Battery	FTZ10S	
	12V-8.6Ah (10 HR)	
	YTZ10S	
	12V-8.6Ah (10 HR)	
Gear ratios	1st	3.285
	2nd	2.105
	3rd	1.600
	4th	1.300
	5th	1.150
	6th	1.043
Reduction ratios (primary / final)	2.029 / 2.733	