


**▲ WARNING**


Improper loading can cause a crash and you may be seriously hurt or killed. See "Load Limits and Guidelines" in your Owner's Manual for complete instructions.

UNLEADED FUEL ONLY  
PREMIUM RECOMMENDED

**CBR1000RR/RA**

TIRE INFORMATION				DRIVE CHAIN		
Cold tire pressures	Front	250	2.50	36	Keep chain adjusted and lubricated 30 mm (1 1/4 in.) Freeplay	
	Rear	290	2.90	42		
Up to 90kg(200lbs) load	Front	250	2.50	36		
	Rear	290	2.90	42		
Tire size	Front	120/70 ZH17 M/C 65W			Read owner's manual.	
	Rear	190/50 ZH17 M/C 73W				
Min. recommend tire center tread depth.	Front	1.5mm (0.06in.)				
Maximum weight capacity	Rear	2.0mm (0.08in.)				
		166kg(366lbs)				

**CBR1000S1**

TIRE INFORMATION				DRIVE CHAIN		
Cold tire pressures	Front	250	2.50	36	Keep chain adjusted and lubricated 30 mm (1 1/4 in.) Freeplay	
	Rear	290	2.90	42		
Tire size	Front	120/70 ZH17 M/C 65W				
	Rear	190/50 ZH17 M/C 73W				
Min. recommend tire center tread depth.	Front	1.5mm (0.06in.)				
Maximum weight capacity	Rear	2.0mm (0.08in.)				
		110kg(243lbs)				

**CBR1000RR/RA**

For your protection, always wear your helmet while riding. Read the owner's manual carefully.

**CBR1000S1**

For your protection, always wear your helmet while riding. Operator only. No passengers. Read the owner's manual carefully.

