

■ Service Data

Tire size	Front	110/70-17M/C 54S
	Rear	140/70-17M/C 66S
Tire type		Bias-ply, tubeless
Recommended Tires	Front	IRC RX-01FD
	Rear	IRC RX-01RZ
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> ) [With less than 200 lb (90 kg) of added weight]
	Rear	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> ) [With more than 200 lb (90 kg) of added weight]
		33 psi (225 kPa, 2.25 kgf/cm <sup>2</sup> )
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	SIMR8A9 (NGK)
Spark plug gap	(non-adjustable)	0.031 to 0.035 in (0.80 to 0.90 mm)
Idle speed		1,400 ± 100 rpm (NO ADJUSTMENT)

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
Engine oil capacity	After draining	1.5 US qt (1.4 liters)
	After draining & engine oil filter change	1.6 US qt (1.5 liters)
	After disassembly	1.9 US qt (1.8 liters)
Recommended brake (clutch) fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	1.16 US qt (1.10 liters)	
Recommended coolant	Pro Honda HP Coolant	