

Specifications

■ Main Components

Overall length	80.1 in (2,035 mm)
Overall width	28.3 in (720 mm)
Overall height	44.1 in (1,120 mm)
Wheelbase	54.3 in (1,380 mm)
Minimum ground clearance	5.7 in (145 mm)
Caster angle	25.1°
Trail	3.9 in (98 mm)
Curb weight	CBR300R 357 lb (162 kg)
	CBR300RA 364 lb (165 kg)
Maximum weight capacity *1	366 lb (166 kg)
Maximum weight in storage compartment *2	6.6 lb (3.0 kg)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	8.2 ft (2.5 m)

*1 : Including rider, passenger, all luggage, and accessories

*2 : Includes the weight of the luggage and added accessories

Displacement	17.4 cu-in (286 cm ³)
Bore x stroke	2.99 x 2.48 in (76.0 x 63.0 mm)
Compression ratio	10.7:1
Fuel	Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher.
Tank capacity	3.43 US gal (13.0 L)
Battery	YTX7L-BS 12 V-6 Ah (10 HR)
Gear ratio	1st 3.416
	2nd 2.250
	3rd 1.650
	4th 1.350
	5th 1.166
	6th 1.038
Reduction ratio (primary / final)	2.807 / 2.571