

# Specifications

## ■ Main Components

Type	PC40
Overall length	79.9 in (2,030 mm)
Overall width	27.0 in (685 mm)
Overall height	43.9 in (1,115 mm)
Wheelbase	53.9 in (1,370 mm)
Minimum ground clearance	5.3 in (135 mm)
Caster angle	23° 55'
Trail	3.9 in (98 mm)
Curb weight	<b>CBR600RR</b>
	50 STATE (meets California)
	412 lb (187 kg)
	49 STATE
	410 lb (186 kg)
	<b>CBR600RA</b>
50 STATE (meets California)	
434 lb (197 kg)	
Canada model	
432 lb (196 kg)	
Maximum weight capacity*1	366 lb (166 kg)

\*1 Including rider, passenger, all luggage, and accessories

\*2 Includes the weight of the luggage and added accessories.

Maximum luggage weight*2	66 lb (30 kg)
	Luggage 31 lb (14 kg) Accessories 35 lb (16 kg)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	10.6 ft (3.2 m)
Displacement	36.5 cu-in (599 cm <sup>3</sup> )
Bore x stroke	2.64 x 1.67 in (67.0 x 42.5 mm)
Compression ratio	12.2:1
Fuel	Unleaded gasoline Recommended: 91 PON or higher
Tank capacity	4.76 US gal (18.0 liters)
Battery	YTZ10S
	12V-8.6Ah (10 HR)
Gear ratios	1st 2.750
	2nd 2.000
	3rd 1.666
	4th 1.444
	5th 1.304
	6th 1.208
Reduction ratios (primary / final)	2.111 / 2.625