

## ■ Service Data

Tyre size	Front	3.00-21 51P
	Rear	120/80-18M/C 62P
Tyre type	Bias-ply, tube	
Recommended Tyres	Front	IRC GP-21F Z
	Rear	IRC GP-22R
Tyre air pressure	Front	150 kPa (1.50 kgf/cm <sup>2</sup> , 22 psi)
	Rear	150 kPa (1.50 kgf/cm <sup>2</sup> , 22 psi)
Minimum tread depth	Front	3.0 mm (0.12 in)
	Rear	3.0 mm (0.12 in)
Spark plug	(standard)	SIMR8A9 (NGK)
Spark plug gap	(non-adjustable)	0.80 to 0.90 mm (0.031 to 0.035 in)
Idle speed	1,450 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	1.4 litres (1.5 US qt, 1.2 Imp qt)
	After draining & filter change	1.5 litres (1.6 US qt, 1.3 Imp qt)
	After disassembly	1.8 litres (1.9 US qt, 1.6 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	1.02 litres (1.08 US qt, 0.90 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	