

Specifications

■ Bulbs

Headlight	LED
Brake light / Taillight	12 V-21 / 5 W
Front turn signal light / Position light	12 V-21 / 5 W
Rear turn signal light	12 V-21 W
License plate light	LED

■ Fuses

Main fuse	30 A
Other fuse	CRF250RL 20 A, 10 A
	CRF250RLA 30 A, 20 A, 10 A

■ Torque Specifications

Hook bolt	15 lbf-ft (21 N·m, 2.1 kgf·m)
Engine oil drain bolt	18 lbf-ft (24 N·m, 2.4 kgf·m)
Oil filter cover bolt	7 lbf-ft (10 N·m, 1.0 kgf·m)
Front axle shaft	51 lbf-ft (69 N·m, 7.0 kgf·m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf·m)
Rear axle nut	65 lbf-ft (88 N·m, 9.0 kgf·m)
Drive chain adjusting lock nut	20 lbf-ft (27 N·m, 2.8 kgf·m)
Tail cap cover bolt	3.9 lbf-ft (5.25 N·m, 0.5 kgf·m)
Spark arrester mounting bolt	6.6 lbf-ft (9 N·m, 0.9 kgf·m)
Muffler cover bolt	1.1 lbf-ft (1.5 N·m, 0.2 kgf·m)