

## Specifications

### ■ Bulbs

|   |                   |
|---|-------------------|
| Headlight                                   | LED               |
| Brake light / Taillight                     | 12 V-21 / 5 W     |
| Front turn signal light /<br>Position light | 12 V-21 / 5 W x 2 |
| Rear turn signal light                      | 12 V-21 W x 2     |
| License plate light                         | LED               |

### ■ Fuses

|            |                                   |
|------------|-----------------------------------|
| Main fuse  | 30 A                              |
| Other fuse | <b>CRF250RL</b> 20 A, 10 A        |
|            | <b>CRF250RLA</b> 30 A, 20 A, 10 A |

### ■ Torque Specifications

|                                |                                  |
|--------------------------------|----------------------------------|
| Hook bolt                      | 15 lbf-ft (21 N-m, 2.1 kgf-m)    |
| Engine oil drain bolt          | 18 lbf-ft (24 N-m, 2.4 kgf-m)    |
| Oil filter cover bolt          | 7 lbf-ft (10 N-m, 1.0 kgf-m)     |
| Front axle shaft               | 51 lbf-ft (69 N-m, 7.0 kgf-m)    |
| Front wheel axle pinch bolt    | 16 lbf-ft (22 N-m, 2.2 kgf-m)    |
| Rear axle nut                  | 65 lbf-ft (88 N-m, 9.0 kgf-m)    |
| Drive chain adjusting lock nut | 20 lbf-ft (27 N-m, 2.8 kgf-m)    |
| Tail cap cover bolt            | 3.9 lbf-ft (5.25 N-m, 0.5 kgf-m) |
| Spark arrester mounting bolt   | 6.6 lbf-ft (9.0 N-m, 0.9 kgf-m)  |
| Muffler cover bolt             | 1.1 lbf-ft (1.5 N-m, 0.2 kgf-m)  |