












Optional Parts List

These parts and tools may be ordered from your Honda dealer.

FRAME	Remarks
Driven sprocket Standard	< >: Drive chain links 51 Teeth, Aluminum. <114>
Optional	50 Teeth, Aluminum <114>
	52 Teeth, Aluminum <116>
Handlebar lower holder	
Standard	3 mm offset
Optional	no offset

TOOLS	Remarks
Pin spanner A 	To adjust spring pre-load. (two spanners required)
Workstand 	For maintenance
Air gauge	For checking tyre air pressure

FRAME	Remarks
Shock spring Standard	5.50 kgf/mm (308.0 lbf/in)  No mark (factory products) or  Red paint (aftermarket parts)
Optional Softer	5.30 kgf/mm (296.8 lbf/in)  Blue paint
Stiffer	5.70 kgf/mm (319.2 lbf/in)  Pink paint 5.90 kgf/mm (330.4 lbf/in)  Silver paint
Fork spring Standard	0.47 kgf/mm (26.32 lbf/in)  No mark (factory products) or  1 scribe mark (aftermarket parts)
Optional Softer	0.45 kgf/mm (25.20 lbf/in)  2 scribe marks
Stiffer	0.49 kgf/mm (27.44 lbf/in)  3 scribe marks

The standard fork spring and shock spring mounted on the motorcycle when it leaves the factory are not marked. Before replacing the springs, be sure to mark them so they can be distinguished from other optional springs.