

## Specifications

Recommended drive chain lubricant	Pro Honda HP Chain lube or equivalent	
Drive chain slack	1 3/16 to 1 9/16 in (30 to 40 mm) DID 520V0 or RK 520KHO	
Standard drive chain	<b>NC700X</b>	
	No. of links	114
	<b>NC700XD</b>	
No. of links	112	
	Engine sprocket	16T
Standard sprocket sizes	<b>NC700X</b>	
	Rear wheel sprocket	43T
	<b>NC700XD</b>	
Rear wheel sprocket	39T	

### ■ Bulbs

Headlight	12V-60/55W
Brake/Tail light	12V-21/5W
Front turn signal lights	12V-21/5W x 2
Rear turn signal lights	12V-21W x 2

### ■ Fuses

Main fuse	30A	
Other fuses	<b>NC700X</b>	15A, 7.5A
	<b>NC700XD</b>	30A, 15A, 7.5A

### ■ Torque Specifications

Maintenance lid screws	2.2 lbf-ft (3 N-m, 0.3 kgf-m)
Engine oil drain bolt	22 lbf-ft (30 N-m, 3.1 kgf-m)
Oil filter	19 lbf-ft (26 N-m, 2.7 kgf-m)
Front wheel axle shaft	55 lbf-ft (74 N-m, 7.5 kgf-m)
Front wheel brake caliper mounting bolts	22 lbf-ft (30 N-m, 3.1 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N-m, 2.2 kgf-m)
Rear wheel axle nut	72 lbf-ft (98 N-m, 10.0 kgf-m)
Drive chain adjusting lock nuts	15 lbf-ft (21 N-m, 2.1 kgf-m)
Parking brake caliper mounting bolts	23 lbf-ft (31 N-m, 3.2 kgf-m)
Brake/tail light assembly screw C	4.4 lbf-ft (6 N-m, 0.6 kgf-m)