

## (VT750C2B)

TIRE INFORMATION		
Cold tire pressures :		
[Up to maximum weight capacity]		
Front	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Rear	250kPa 2.50kg/cm <sup>2</sup> 36psi	
[Up to 90kg(200lbs) load]		
Front	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Rear	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Maximum weight capacity : 182kg(401lbs)		
Tire size : Front 120/90-17M/C 64S		
Rear 160/85-15M/C 74S		
Tire brand	Front	Rear
DUNLOP	D404FG	8404
BRIDGESTONE	G701	G702
CHEUNG SHIN	M6002	M6011R
Min. recommend tire center tread depth.		
Front 1.5mm (0.06in.)		Rear 2.0mm (0.08in.)
Read owner's manual.		

## (VT750C2/C2F/C2S)

TIRE INFORMATION		
Cold tire pressures:		
[Up to maximum weight capacity]		
Front	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Rear	250kPa 2.50kg/cm <sup>2</sup> 36psi	
[Up to 90kg(200lbs) load]		
Front	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Rear	200kPa 2.00kg/cm <sup>2</sup> 29psi	
Maximum weight capacity: 180kg(397lbs)		
Tire size: Front 90/90-21M/C 54S		
Rear 160/85-15M/C 74S		
Tire brand	Front	Rear
DUNLOP	D404F	D404
BRIDGESTONE	EXEDRA G701	EXEDRA G702
Min. recommend tire center tread depth.		
Front 1.5mm(0.06in.)		Rear 2.0mm(0.08in.)
Read owner's manual.		

