

Spark plugs	(standard)	DPR7EA-9 (NGK) or X22EPR-U9 (DENSO)
	(high speed riding)	DPR8EA-9 (NGK) or X24EPR-U9 (DENSO)
Spark plug gap	(non-adjustable)	0.031 to 0.035 in (0.80 to 0.90 mm)
Idle speed		1,200 ± 100 rpm
Recommended engine oil		API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil
Engine oil capacity	After draining	2.6 US qt (2.5 liters)
	After draining & filter change	2.7 US qt (2.6 liters)
	After disassembly	3.4 US qt (3.2 liters)
Recommended final drive oil		Hypoid gear oil SAE 80
Final drive oil capacity	After draining	5.4 US oz (160 cm <sup>3</sup> )
	After disassembly	5.7 US oz (170 cm <sup>3</sup> )
Recommended brake fluid		Honda DOT 4 Brake Fluid
Cooling system capacity		2.07 US qt (1.96 liters)
Recommended coolant		Pro Honda HP Coolant

## ■ Bulbs

Headlight	12V-60/55W
Brake/Taillight	12V-21/5W
Front turn signal lights	12V-21/5W x 2
Rear turn signal lights	12V-21W x 2
License plate light	12V-5W

## ■ Fuses

Main fuse		30A
FI fuse	<b>VT750C2/C2F/C2B</b>	15A
	<b>VT750C2S</b>	20A
Other fuses	<b>VT750C2/C2F/C2B</b>	20A, 10A
	<b>VT750C2S</b>	30A, 20A, 10A