

Specifications

■ Main Components

Type	XL125LEK	JD21
	XR125LEK	
	XR150LEK	KD07
Overall length	XR125LEK	2,100 mm (82.7 in)
	XR150LEK	
	XL125LEK	2,115 mm (83.3 in)
Overall width	XR125LEK	820 mm (32.3 in)
	XR150LEK	
	XL125LEK	825 mm (32.5 in)
Overall height	XR125LEK	1,125 mm (44.3 in)
	XR150LEK	
	XL125LEK	1,145 mm (45.1 in)
Wheelbase	XL125LEK	1,355 mm (53.3 in)
	XR125LEK	
	XR150LEK	1,360 mm (53.5 in)
Minimum ground clearance	XR125LEK	245 mm (9.6 in)
	XR150LEK	
	XL125LEK	260 mm (10.2 in)
Caster angle	XR125LEK	27° 0'
	XR150LEK	
	XL125LEK	26° 8'
Trail	XR125LEK	104 mm (4.1 in)
	XR150LEK	
	XL125LEK	103 mm (4.1 in)

*1 Including driver, passenger, all luggage, and accessories.

Curb weight	XL125LEK	127 kg (280 lb)
	XR125LEK	128 kg (282 lb)
	XR150LEK	129 kg (284 lb)
Maximum weight capacity*1		155 kg (342 lb)
Maximum weight on rear carrier		5.0 kg (11.0 lb)
Passenger capacity		Driver and 1 passenger
Minimum turning radius		2.1 m (6.9 ft)
Displacement	XL125LEK	125 cm ³ (7.63 cu-in)
	XR125LEK	
	XR150LEK	149 cm ³ (9.09 cu-in)
Bore × stroke	XL125LEK	52.4 × 57.8 mm
	XR125LEK	(2.06 × 2.28 in)
	XR150LEK	57.3 × 57.8 mm
		(2.26 × 2.28 in)
Compression ratio	XL125LEK	9.2:1
	XR125LEK	
	XR150LEK	9.5:1
Fuel		Unleaded petrol Recommended: 91 RON or higher
Tank capacity		12.0 litres (3.17 US gal, 2.64 Imp gal)
Battery		YTX5L-BS
		12V-4Ah (10HR)