

## Specifications

### Service Data

<b>CFT125MR/MS</b>	
Front	2.50-17 43L
Rear	2.50-17 43L
<b>CFT125MRC</b>	
Front	70/90-17M/C 38P
Rear	80/90-17M/C 50P
<b>CFT125MR/MS</b>	
Front	3.0 mm (0.12 in)
Rear	3.0 mm (0.12 in)
Tyre type	
Bias-ply, tube	
<b>CFT125MR/MS</b> MBP MM-102B	
Front	<b>CFT125MRC</b> MBP MP-220
<b>CFT125MR/MS</b> MBP MM-102B	
Rear	<b>CFT125MRC</b> MBP MP-221
Tyre air pressure	
[Rider only]	
Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
[Rider and 1 passenger]	
Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
[Rider only]	
Rear	225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
[Rider and 1 passenger]	
Rear	<b>CFT125MR/MS</b> 280 kPa (2.80 kgf/cm <sup>2</sup> , 41 psi)
<b>CFT125MRC</b> 250 kPa (2.50 kgf/cm <sup>2</sup> , 36 psi)	

Spark plug (standard)	CPR7EA-9 (NGK) or U22EPR9 (DENSO)
Spark plug gap	0.8 to 0.9 mm (0.03 to 0.04 in)
Idle speed	1,400 ± 100 rpm
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," or "Resource Conserving" SAE 10W-30, JASO T 903 standard MA
Engine oil capacity	After draining 0.7 litres (0.7 US qt, 0.6 Imp qt)
After disassembly	0.9 litres (1.0 US qt, 0.8 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid
Recommended drive chain lubricant	Drive chain lubricant If not available, use SAE 80 or 90 gear oil.
Drive chain slack	25 to 35 mm (1.0 to 1.2 in)
Standard drive chain	DID420AD2 KMC420JB RK420SL
No. of links	104
Standard sprocket	14T
Driven sprocket	38T

## Specifications