

SPECIFICATIONS

GENERAL		
	ITEM	SPECIFICATIONS
DIMENSIONS	Overall length	2,125 mm (83.7 in)
	Overall width	750 mm (29.5 in)
	Overall height	1,085 mm (42.7 in)
	Wheelbase	1,460 mm (57.5 in)
	Seat height	795 mm (31.3 in)
	Footpeg height	345 mm (13.6 in)
	Ground clearance	145 mm (5.7 in)
	Dry weight	Except California type California type
Curb weight	Except California type California type	218 kg (481 lbs) 219 kg (483 lbs)
	Maximum weight capacity	174 kg (384 lbs)
FRAME	Frame type	Diamond
	Front suspension	Telescopic fork
	Front axle travel	109 mm (4.3 in)
	Rear suspension	Swingarm
	Rear axle travel	128 mm (4.7 in)
	Front tire size	120/70 ZR 17 (58W), 120/70 ZR 17 M/C (58W)
	Rear tire size	180/55 ZR 17 (73W), 180/55 ZR 17 M/C (73W)
	Front tire brand	BT56F RADIAL N (Bridgestone) TX15 (Michelin)
	Rear tire brand	BT56R RADIAL G (Bridgestone) TX25 (Michelin)
	Front brake	Hydraulic double disc
	Rear brake	Hydraulic single disc
	Caster angle	25°
	Trail length	98 mm (3.9 in)
	Fuel tank capacity	19.0 liter (5.02 US gal, 4.18 Imp gal)
ENGINE	Cylinder arrangement	4 cylinders in-line, inclined 30° from vertical
	Bore and stroke	71.0 X 58.0 mm (2.80 X 2.28 in)
	Displacement	919 cm ³ (56.1 cu-in)
	Compression ratio	10.8 : 1
	Valve train	Chain driven, DOHC
	Intake valve	opens — at 1 mm closes — (0.04 in) lift
	Exhaust valve	opens — closes —
	Lubrication system	Forced pressure and wet sump
	Oil pump type	Trochoid
	Cooling system	Liquid cooled
	Air filtration	Paper element
	Engine dry weight	68 kg (150 lbs)
	Firing order	1 - 2 - 4 - 3