

## GENERAL INFORMATION

Unit: mm (in)

### FRONT WHEEL/SUSPENSION/STEERING

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		—	1.5 (0.06)
Cold tire pressure	Driver only	250 kPa (2.50 kgf/cm <sup>2</sup> , 36 psi)	—
	Driver and passenger	250 kPa (2.50 kgf/cm <sup>2</sup> , 36 psi)	—
Axle runout		—	0.2 (0.01)
Wheel rim runout	Radial	—	2.0 (0.08)
	Axial	—	2.0 (0.08)
Wheel balance weight		—	60 g (2.1 oz) max.
Fork	Spring free length	282.3 (11.1)	276.7 (10.89)
	Tube runout	—	0.20 (0.008)
	Recommended fork fluid	Pro Honda Suspension Fluid SS-8	—
	Fluid level	155 (6.1)	—
Fluid capacity		463 ± 2.5 cm <sup>3</sup> (15.7 ± 0.08 US oz, 16.3 ± 0.09 Imp oz)	—
Steering head bearing pre-load		10 – 15 N•m (1.0 – 1.5 kgf)	—

### REAR WHEEL/SUSPENSION

Unit: mm (in)

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		—	2.0 (0.08)
Cold tire pressure	Driver only	290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	—
	Driver and passenger	290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	—
Axle runout		—	0.2 (0.01)
Wheel rim runout	Radial	—	2.0 (0.08)
	Axial	—	2.0 (0.08)
Wheel balance weight		—	60 g (2.1 oz) max.
Drive chain	Size/link	DID	DID50VA8-114LE
		RK	RK50HFOZ5-114LE
	Slack	30 – 40 (1.2 – 1.6)	