

NOTE

- Do not depress the brake lever when the calipers are removed, or it will be difficult to refit the disc between the brake pads.
- If you plan to disassemble the forks legs, loosen the top bridge bolts first then the fork cap bolts but do not remove them at this time.
- Suspend the right and left handlebars properly so that the cables and wires are not bent tightly.

Requisite Service

- Front wheel removal (page 12-4)

Procedure		Q'ty	Remarks
Removal Order			
(1)	Stopper ring	2	
(2)	Handlebar pinch bolt	2	
(3)	Right/Left handlebar assembly	1/1	
(4)	Front brake caliper assembly	2	Be careful not to damage the brake pipe.
(5)	Socket bolt	2	
(6)	Front fender	1	
(7)	Top bridge pinch bolt	2	
(8)	Bottom bridge pinch bolt	2	Be sure to hold the fork leg while loosening the bolts.
(9)	Fork leg assembly	2	
Installation Order			
(9)	Fork leg assembly	2	Install the fork leg assembly so that the distance between the fork pipe upper edge and upper surface of the fork top bridge is 41 mm (1.6 in).
(8)	Bottom bridge pinch bolt	2	
(7)	Top bridge pinch bolt	2	
(6)	Front fender	1	
(5)	Socket bolt	2	
(4)	Front brake caliper assembly	2	
(3)	Right/Left handlebar assembly	2	Align the handlebar boss with the top bidge slot.
(2)	Handlebar pinch bolt	2	Tighten the pinch bolt while pushing the handlebar forward.
(1)	Stopper ring	2	