			1	6	12	
WHEEL	Tire Pressures	●		●	●	
	Tire wear and damage	●		●	●	
	Tire tread depth	●		●	●	Min - Frt 0.8mm Rear 0.8mm
	Foreign articles stuck in tires	●		●	●	
	Wheel nut, wheel bolt loosening			●	●	Tighten axle nut, axle holder front axle holder torque 1.8-2.5 Kg.m Fro axle bolt torque 5.5-6.5 Kg.m Rr axle nut torque 8.5-10.5 Kg.m
	Rim, side rim, wheel disc damage		○		●	Wheel rim runout, warpage Front 2.0mm axial 2.0mm radial Rear 2.0mm axial 2.0mm radial
	Front wheel bearings				●	
	Rear wheel bearing				●	
Swing Arm	Damage				●	Tighten cushion, spring
	Arm damage				●	
Shock Ab	Fluid leakage, damage				●	
	Bushese				●	
Clutch	Lever play			●	●	Play - lever 10-20mm
	Use		○	●	●	
Trans	Fluid leakage, oil capacity			●	●	Oil capacity - between upper and lower marks
	Gear movement				●	
Oil	Transmission oil replacement					Every two years

	Frt	Rear
1 rider	2.25	2.25
	2.25	2.25
2 riders	2.25	2.50
Tire type	110/70R17 54H	150/60R18 67H